



Rotary dimmer, 1000W, 1G, 1-way, tungsten, white interior

Part no. **C9511**
 Catalog No. **175054**
 Alternate Catalog No. **C9511**

Delivery program

Product Range			Copa
COPA insert			White Insert
Function			Dimmers
Current rating	Amperage		150 - 1000 W
Rated operating voltage	Volts		200-250V~ μ
No. of gang			1 Gang
Switch type			1 Way
Types conform to (Standards)			BS EN 60669-2-1 BS EN 60669-1 IEC 60669-2-1 IEC 60669-1
Front plate colour			White
Front plate material			Thermoplastic
Front plate / module dimensions		mm	84 x 84
Front plate depth		mm	6.5
Fixing Centres		mm	60.3
Recommended Minimum back box depth		mm	35
Weight (kgs)		kgs	0.074
Terminal material			Brass
Terminal Screw Details			Zinc Coated Steel with clear Passivation
Terminal capacity (L.N & E)		mm ²	4 x 1.0mm ² or 3 x 1.5mm ² or 1 x 2.5mm ²
Terminal screw head design			Slotted Head

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Dimmer (EC000025)			
Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Dimmer (ecl@ss10.0.1-27-14-40-14 [AJZ710013])			
Assembly arrangement			Basic element with full cover plate
Method of operation			Turn button
Number of modules (module system)			0
App control via Bluetooth			No
Dimming phase cut-on			No
Dimming phase cut-off			Yes
Serial dimmer			No
Type of load			Universal
Substation input			No
Light value memory			Yes
Applicable with button			Yes
Applicable with movement sensor			No
Applicable with presence indicator			No
Applicable with time switch/timer			No
Applicable with transmission button			No
Applicable with infrared button			No
Mounting method			Flush mounted (plaster)
Type of fastening			Mounting with screw
Material			Plastic
Material quality			Duroplast

Halogen free		Yes
Surface protection		Untreated
Surface finishing		Matt
Colour		White
RAL-number (akin)		0
Transparent		No
Suitable for degree of protection (IP)		IP3X
Impact strength		IK00
Nominal voltage	V	220 - 250
Frequency	Hz	50 - 50
Control voltage	V	60 - 240
Nominal power	VA	300 - 1000
Connection type		Screw terminal
Core cross section	mm ²	1 - 2.5
Width of device	mm	86
Height of device	mm	86
Depth of device	mm	45
Min. depth of built-in installation box	mm	35