



Fused disconnector, low voltage, 600 A, DC 60 V, 1P, UL

Catalog No. 15100-604

Similar to illustration

Delivery program

Product range			Control
Basic function			Fused disconnector
Field of application			low voltage
Rated current	I	A	600
Rated voltage			DC 60 V
Description			Panel Mounting
Breaking Capacity		kA	100
Number of poles			1P
usable for size/applications			Telecommunications DC power circuit protection for TPL fuse-links
Standard/Approval			UL
Standards/Regulations			UL 1801

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecI@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC		V	60
Rated permanent current Iu		A	600
Rated operation power at AC-23, 400 V		kW	
Conditioned rated short-circuit current Iq		kA	100
Rated short-time withstand current Icw		kA	100
Suitable for fuses			Other
Number of poles			2
With error protection			No
Type of electrical connection of main circuit			
Cable entry			
Equipped with connectors			Yes
Suitable for ground mounting			No
Suitable for front mounting 4-hole			No
Suitable for busbar mounting			Yes
Type of control element			
Position control element			
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			