



**Fused disconnector, low voltage, 70 A, DC 60 V, UL**

**Catalog No. 15800-F-200**

Similar to illustration

## Delivery program

Product range			Control
Basic function			Fused disconnector
Field of application			low voltage
Rated current	I	A	70
Rated voltage			DC 60 V
Description			Front panel mounting
Breaking Capacity		kA	100
usable for size/applications			Telecommunications DC power circuit protection for TPS fuse-links
Standard/Approval			UL
Optional accessories			fuse holders TPSFH-AS and TPSFH-T

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ec1@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			No
Version as safety switch			No
Max. rated operation voltage Ue AC		V	60
Rated permanent current Iu		A	70
Rated operation power at AC-23, 400 V		kW	
Conditioned rated short-circuit current Iq		kA	100
Rated short-time withstand current Icw		kA	
Suitable for fuses			Other
Number of poles			2
With error protection			No
Type of electrical connection of main circuit			Cable clamp
Cable entry			
Equipped with connectors			Yes
Suitable for ground mounting			No
Suitable for front mounting 4-hole			No
Suitable for busbar mounting			Yes
Type of control element			
Position control element			
Motor drive optional			No
Motor drive integrated			No
Version as emergency stop installation			No
Degree of protection (IP), front side			