



**Socket outlet, 13A, 2G, unswitched, stainless steel**

**Part no. B112SS**  
**Catalog No. B112SS**

## Delivery program

Product Range			Copa Fix
Function			Sockets
Current rating	Amperage		13 A
Rated operating voltage	Volts		250V~
No. of gang			2 Gang
Types conform to (Standards)			BS 1363-2
Front plate colour			Stainless Steel
Front plate material			Stainless Steel
Base colour			Grey
Base material			Thermoplastic
Front plate / module dimensions		mm	148 x 87
Front plate depth		mm	5.8
Fixing Centres		mm	120.6
Recommended Minimum back box depth		mm	25
Weight (kgs)		kgs	0.139
Contact material			Silver Nickel
Terminal material			Brass
Terminal Screw Details			Zinc Coated Steel with clear Passivation
Terminal capacity (L.N & E)		mm <sup>2</sup>	L, N & E in Base = 2 x 4.0mm <sup>2</sup> or 1 x 6.0mm <sup>2</sup> Earth on Strap = 1 x 4.0mm <sup>2</sup> or 1 x 6.0mm <sup>2</sup>
Terminal screw head design			Combination Head
IP Rating			IP20
Finish / Color			Stainless Steel

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Socket outlet (EC000125)			
Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Plug socket (ecl@ss10.0.1-27-14-40-42 [AKE352014])			
Model			British Standard
Protective contact			Yes
Protective earth pin round			No
Number of active Pins (round)			0
Number of active Pins (flat)			0
With signal lamp			No
With built-in USB power supply			No
Number of units			1
Number of modules (module system)			0
Number of socket outlets switchable			2
Number of phases			2
Imprint/indication			Other
Connection type			Screwed terminal
With hinged lid			No
With child-protection			Yes
Label space/information surface			No
Colour			Stainless steel

RAL-number (akin)			0
Transparent			No
Lockable			No
Eject-mechanism			No
Insulated mounting			No
With function lighting			No
With orientation lighting			No
Over voltage protection			No
Fault current protection			No
With miniature fuse			No
Special power supply			No special power supply
Mounting method			Flush mounted (plaster)
Type of fastening			Mounting with screw
Material			Metal
Material quality			Stainless steel
Halogen free			Yes
Surface protection			Lacquered
Surface finishing			Matt
Antibacterial treatment			Yes
With on/off switch			No
With loop through function			Yes
Rotated central insert			No
Nominal current		A	13
Nominal voltage		V	240
Frequency		Hz	50 - 50
Rated fault current		mA	250
Suitable for degree of protection (IP)			IP66
For heavy conditions (in accordance with VDE)			No
Impact strength			IK00
Width of device		mm	146
Height of device		mm	86
Depth of device		mm	35
Min. depth of built-in installation box		mm	25