



Fused connection unit, 13A, switched, neon, stainless steel

Part no. B221NSS
Catalog No. B221NSS



Delivery program

Product Range			Copa Fix
Function			Connection Units
Current rating	Amperage		13 A
Rated operating voltage	Volts		250V~
No. of gang			1 Gang
Switch type			Double Pole
Types conform to (Standards)			BS 1363-4
Front plate colour			Stainless Steel
Front plate material			Stainless Steel
Rocker colour			White
Rocker material			Urea
Base colour			Grey
Base material			Thermoplastic
Front plate / module dimensions		mm	87 x 87
Front plate depth		mm	5.8
Fixing Centres		mm	60.3
Recommended Minimum back box depth		mm	25
Weight (kgs)		kgs	0.108
Contact material			Silver Nickel
Terminal material			Brass
Terminal Screw Details			Zinc Coated Steel with clear Passivation
Terminal capacity (L.N & E)		mm ²	L + N = 4 x 2.5mm ² or 2 x 4.0mm ² - E = 3 x 2.5mm ² or 1 x 4.0mm ²
Terminal screw head design			Combination Head
IP Rating			IP20
Finish / Color			Stainless Steel

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Appliance connector (EC003546)			
Nominal current		A	13
Colour			Grey
Model			Coupler
Standard			Other