DATASHEET - B221SS



Fused connection unit, 13A, switched, stainless steel

Powering Business Worldwide*

Part no. B221SS Catalog No. B221SS

Delivery program

| Delivery program | | | |
|------------------------------------|----------|-----|--------------------------------------------------------------------------------------------------------------------------|
| Product Range | | | Copa Fix |
| Function | | | Connection Units |
| Current rating | Amperage | | 13 A |
| Rated operating voltage | Volts | | 250V~ |
| No. of gang | | | 1 Gang |
| Switch type | | | Double Pole |
| Types conform to (Standards) | | | BS 1363-4 |
| Front plate colour | | | Stainless Steel |
| Front plate material | | | Stainless Steel |
| Rocker colour | | | White |
| Rocker material | | | Urea |
| Base colour | | | Grey |
| Base material | | | Thermoplastic |
| Front plate / module dimensions | | mm | 87 x 87 |
| Front plate depth | | mm | 5.8 |
| Fixing Centres | | mm | 60.3 |
| Recommended Minimum back box depth | | mm | 25 |
| Weight (kgs) | | kgs | 0.104 |
| Contact material | | | Silver Nickel |
| Terminal material | | | Brass |
| Terminal Screw Details | | | Zinc Coated Steel with clear Passivation |
| Terminal capacity (L.N & E) | | mm² | L + N = 4 x 2.5mm ² or 2 x 4.0mm ² - E = 3 x 2.5mm ² or 1 x 4.0mm ² |
| Terminal screw head design | | | Combination Head |
| IP Rating | | | IP20 |
| Finish / Color | | | Stainless Steel |

Technical data ETIM 7.0

| Domestic switching devices (EG000013) / Appliance connector (EC003546) | | | | |
|------------------------------------------------------------------------|---|---------|--|--|
| Nominal current | Α | 13 | | |
| Colour | | Grey | | |
| Model | | Coupler | | |
| Standard | | Other | | |