



Switch, 50A, 2p, neon, marked 'cooker', stainless steel

Part no.

B426NSS

Catalog No.

B426NSS

Delivery program

Product Range			Copa Fix
Function			Switches
Current rating	Amperage		50 A
Rated operating voltage	Volts		250V~
No. of gang			1 Gang
Switch type			Double Pole
Types conform to (Standards)			BS 4177
Front plate colour			Stainless Steel
Front plate material			Stainless Steel
Rocker colour			White
Rocker material			Urea
Base colour			Grey
Base material			Thermoplastic
Front plate / module dimensions		mm	87 x 87
Front plate depth		mm	5.8
Fixing Centres		mm	60.3
Recommended Minimum back box depth		mm	47
Weight (kgs)		kgs	0.196
Contact material			Silver Nickel
Terminal material			Brass
Terminal Screw Details			Zinc Coated Steel with clear Passivation
Terminal capacity (L.N & E)		mm ²	3 x 4.0mm ² or 2 x 6.0mm ² or 1 x 10.0mm ²
Terminal screw head design			Combination Head
IP Rating			IP20
Finish / Color			Stainless Steel

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Switch (EC001590)			
Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Switch (ecl@ss10.0.1-27-14-40-53 [ACN451011])			
Wiring system			Two-way switch
Method of operation			Rocker/button
Assembly arrangement			Basic element with full cover plate
Number of modules (module system)			0
Push button switch			Yes
Number of rockers			1
Mounting method			Flush mounted (plaster)
Type of fastening			Screw mounting
With mounting plate			No
Material			Metal
Material quality			Stainless steel
Halogen free			Yes
Surface protection			Lacquered
Surface finishing			Matt
Colour			Stainless steel
RAL-number (akin)			0

Label space/information surface		No
Illumination		Yes
Function lighting		Illuminated (on)
Type of lighting		Not included
Suitable for degree of protection (IP)		IP3X
Nominal voltage	V	240
Rated current	A	50
Switching current for fluorescent lamps	AX	50
Feedback-signal contact		No
Connection type		Screwed terminal
Washing machine switch		No
Width of device	mm	86
Height of device	mm	86
Depth of device	mm	45
Built-in depth	mm	25
Min. depth of built-in installation box	mm	47