

**Profile terminal 41x20-42**

Part no. AKP800
Catalog No. 107198

EL-Nummer 2465036
(Norway)

Delivery program

Product range			60 mm system 185 mm system
Subrange			Profile terminals
Description			Termination to busbars without drilling Put a spacer between the laminated copper busbars when connecting in parallel
Width		mm	72
Rated operational current	I _e	A	1600
conductor			800 mm ² , terminal area 41 x 20 - 42 mm ■ #
Cu factor		kg	0,20
For use with			Double T profile
Notes <p>○ round conductor, solid</p> <p>⦿ Flexible, round conductor with correctly crimped ferrule</p> <p>Round conductor, stranded</p> <p>💡 Section conductor, solid</p> <p>Sector conductor, stranded</p> <p># CU band</p> <p>■ CU busbar</p>			

Approvals

Product Standards			UL508A; CSA-C22.2 No. 14; IEC 60439-1; CE marking
UL File No.			E307559
UL Category Control No.			NMTR2, NMTR8
CSA File No.			236217
CSA Class No.			3211-37
North America Certification			UL recognized, CSA certified
Conditions of Acceptability			Refer to approbation report
Specially designed for North America			No
Suitable for			Feeder circuits
Current Limiting Circuit-Breaker			Refer to approbation report
Max. Voltage Rating			600 V AC
Degree of Protection			Feeder circuits