


**Socket outlet, 13A, 1G, unswitched, black interior**
**Part no. C111BA**  
**Catalog No. C111BA**

## Delivery program

Product Range			Copa
COPA insert			Black Insert
Function			Sockets
Current rating	Amperage		13 A
Rated operating voltage	Volts		250V~
No. of gang			1 Gang
Types conform to (Standards)			BS 1363-2
Front plate colour			Black
Front plate material			Thermoplastic
Base colour			Grey
Base material			Thermoplastic
Front plate / module dimensions		mm	84 x 84
Front plate depth		mm	6.5
Fixing Centres		mm	60.3
Recommended Minimum back box depth		mm	25
Weight (kgs)		kgs	0.05
Contact material			Silver Nickel
Terminal material			Brass
Terminal Screw Details			Zinc Coated Steel with clear Passivation
Terminal capacity (L,N & E)		mm <sup>2</sup>	L, N & E in Base = 2 x 4.0mm <sup>2</sup> or 1 x 6.0mm <sup>2</sup>
Terminal screw head design			Combination Head
IP Rating			IP20

## Technical data ETIM 7.0

Domestic switching devices (EG000013) / Socket outlet (EC000125)			
Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Plug socket (ecl@ss10.0.1-27-14-40-42 [AKE352014])			
Model			British Standard
Protective contact			Yes
Protective earth pin round			No
Number of active Pins (round)			0
Number of active Pins (flat)			0
With signal lamp			No
With built-in USB power supply			No
Number of units			1
Number of modules (module system)			0
Number of socket outlets switchable			1
Number of phases			2
Imprint/indication			Other
Connection type			Screwed terminal
With hinged lid			No
With child-protection			Yes
Label space/information surface			No
Colour			Black
RAL-number (akin)			0
Transparent			No

Lockable		No
Eject-mechanism		No
Insulated mounting		No
With function lighting		No
With orientation lighting		No
Over voltage protection		No
Fault current protection		No
With miniature fuse		No
Special power supply		No special power supply
Mounting method		Flush mounted (plaster)
Type of fastening		Mounting with screw
Material		Plastic
Material quality		Duroplast
Halogen free		Yes
Surface protection		Untreated
Surface finishing		Matt
Antibacterial treatment		No
With on/off switch		No
With loop through function		Yes
Rotated central insert		No
Nominal current	A	13
Nominal voltage	V	240
Frequency	Hz	50 - 50
Rated fault current	mA	250
Suitable for degree of protection (IP)		IP3X
For heavy conditions (in accordance with VDE)		No
Impact strength		IK00
Width of device	mm	86
Height of device	mm	86
Depth of device	mm	40
Min. depth of built-in installation box	mm	25