DATASHEET - X924MG



Cover plate, 24 module, c/w mounting frame

Part no. X924MG Catalog No. X924MG



Delivery program

| Product Range | | | Xtra Surface Metal |
|------------------------------------|-------|-----|--|
| Function | | | Premera Mix Module Plates |
| Rated operating voltage | Volts | | 250V~ |
| No. of gang | | | 24 Gang |
| Types conform to (Standards) | | | BS 5733 |
| Front plate colour | | | Grey (Epoxy Powder Coating for Corrosion Resistance) |
| Front plate material | | | High Quality Steel |
| Front plate / module dimensions | | mm | 198 x 257 |
| Front plate depth | | mm | 6 |
| Fixing Centres | | mm | 180.90 x 60.3 x 60.3 x 60.3 |
| Recommended Minimum back box depth | | mm | 35 |
| Weight (kgs) | | kgs | 0.625 |
| Terminal material | | | Brass |
| Terminal Screw Details | | | Zinc Coated Steel with clear Passivation |
| Terminal capacity (L.N & E) | | mm² | 4 x 2.5mm ² or 2 x 4.0mm ² |
| Terminal screw head design | | | Combination Head |

Technical data ETIM 7.0

| Technical data Ethin 7.0 | Technical data ETIM 7.0 | | | | | |
|--|-------------------------|----|----------------|--|--|--|
| Domestic switching devices (EG000013) / Cover frame for domestic switching devices | ces (EC000007) | | | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Installation switch set / Cover frame (ecl@ss10.0.1-27-14-40-01 [AAB932014]) | | | | | | |
| Number of units | | | 1 | | | |
| Mounting direction | | | Horizontal | | | |
| Number of units horizontal | | | 0 | | | |
| Number of units vertical | | | 0 | | | |
| Number of modules horizontal (module system) | | | 0 | | | |
| Number of modules vertical (module system) | | | 0 | | | |
| Number of gangs | | | 24 | | | |
| With mounting grid | | | Yes | | | |
| Suitable for flush-mounted installation | | | Yes | | | |
| Suitable for floor box | | | No | | | |
| Suitable for wall duct | | | No | | | |
| Suitable for built-in installation | | | Yes | | | |
| Label space/information surface | | | No | | | |
| Material | | | Metal | | | |
| Material quality | | | Aluminium | | | |
| Halogen free | | | Yes | | | |
| Surface protection | | | Lacquered | | | |
| Surface finishing | | | Matt | | | |
| Colour | | | Aluminium | | | |
| RAL-number (akin) | | | 0 | | | |
| Transparent | | | No | | | |
| With hinged lid | | | No | | | |
| Degree of protection (IP) | | | IP3X | | | |
| Impact strength | | | IK00 | | | |
| Type of fastening | | | Screw mounting | | | |
| Width | | mm | 200 | | | |

| Height | n | nm | 15 |
|------------------------------|---|----|-----|
| Depth | m | mm | 260 |
| Built-in width | m | mm | 198 |
| Built-in height | m | mm | 257 |
| Diameter bore hole (opening) | m | nm | 0 |