

**Rapid Link M12-Y sensor distributor**

Part no. RA-XM12-Y
Catalog No. 290424
Alternate Catalog No. RA-XM12-Y

Delivery program

Product range		AS-Interface connection and sensors
Subrange		Y connector
Basic function		For connecting up to 2 sensors per M12 socket
For use with		
For use with		RASP

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	0

Technical data ETIM 7.0

Sensors (EG000026) / Sensor actuator adapter (EC002925)		
Electric engineering, automation, process control engineering / Connector system / Industry connector / Sensor actuator adapter (ecl@ss10.0.1-27-44-01-06 [AFR417003])		
Model		Y-adapter
Contact type		Female
Screened		No
Number of poles		4
Material housing		Metal/plastic
Ambient temperature	°C	0 - 85
Operation temperature	°C	0 - 50
Degree of protection (IP), mounted		IP67
Material thread ring		Stainless steel
Rated voltage	V	24
Rated current In	A	1
Inflammability class of insulation material acc. with UL94		Other
Pollution degree		3
Material of contact surface		Other

Additional product information (links)

IL03406020Z Rapid Link: Speed Control Unit	
IL03406020Z Rapid Link: Speed Control Unit	https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03406020Z2018_05.pdf
MN03406003Z Rapid Link 4.0	
MN03406003Z Rapid Link 4.0 - Deutsch	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_DE.pdf
MN03406003Z Rapid Link 4.0 - English	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_EN.pdf
MN03406003Z Rapid Link 4.0 - français	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_FR.pdf
CA04020001Z-EN Product Range Catalog: Efficient Engineering for Starting and Controlling Motors	http://www.eaton.eu/DE/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238.pdf