

DATASHEET - RA-C1-COV



Protective cover, for link

Part no. RA-C1-COV
Catalog No. 254693
Alternate Catalog No. RA-C1-COV



Delivery program

Product range			Power supply at flat cable RA-C1
Subrange			Protection cover
Basic function			for protecting the 400 V AC/24 V DC flexible busbar junction
For use with			
For use with			RA-C1-PLF

Technical data

General

Ambient temperature			
Operation	8	°C	-30 - +55
Storage	8	°C	-40 - +70
Mounting position			As required

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-30
Operating ambient temperature max.		°C	55

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl:ss10.0.1-27-37-13-92 [AKN570013])			
Type of accessory			Cover

Additional product information (links)

IL03406020Z Rapid Link: Speed Control Unit	
IL03406020Z Rapid Link: Speed Control Unit	https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL03406020Z2018_05.pdf
MN03406003Z Rapid Link 4.0	
MN03406003Z Rapid Link 4.0 - Deutsch	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_DE.pdf
MN03406003Z Rapid Link 4.0 - English	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_EN.pdf
MN03406003Z Rapid Link 4.0 - français	https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN03406003Z_FR.pdf
CA04020001Z-EN Product Range Catalog: Efficient Engineering for Starting and Controlling Motors	http://www.eaton.eu/DE/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct_1095238.pdf