



Isolating blade set, D02, 63A, 400 V

Part no.

Z-SLS/TR-SET

Catalog No.

100660

Delivery program

Product range			Fuse material
Basic function			Accessories
Basic function			Disconnector kit
For use with			Z-SLS/NE0Z Z-SLK/NE0Z Z-SLS/CEK
			Snap-fit on DIN rail 1 set consists of: 3 switch conversion sets, 3 current codings, 1 plastic box The fuse switch-disconnector is thus converted to a switch-disconnector
Rated uninterrupted current	I_u	A	63

Technical data

Electrical

Rated operational voltage	U_e	V	
Rated operating voltage	U_e	V AC	400
Test voltage		kV	5
Rated uninterrupted current	I_u	A	63

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	63
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	1
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
			0

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Accessories for low-voltage switch technology (EC002498)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switch technology (accessories) (ecl@ss10.0.1-27-37-13-92 [AKN570013])

Type of accessory		Contact set
-------------------	--	-------------