




Shunt release, up to 40 A, 110-415V, 1HP

Part no. FAZ-XAA-NA110-415VAC
Catalog No. 102036
Alternate Catalog No. FAZ-XAA-NA110-415VAC

Delivery program

Basic function		Accessories for miniature circuit-breaker
Basic function accessories		Shunt release
Application		Switchgear for 110-V systems
Product range		Accessory
Side mounting		for fitting on left to: FAZ-NA, FAZ-RT
Contact sequence		

Technical data

Electrical

Voltage range		V AC	110 - 415
Rated frequency	f	Hz	50/60

Mechanical

Standard front dimension		mm	45
Enclosure height		mm	105
Mounting width		mm	17.5
Mounting			Quick attachment with 2 latch positions for top-hat rail EN 50022
Degree of protection			
Integrated			IP40
Terminal protection			Busbar tag shroud to BGV A3
Terminals			Twin-purpose terminals

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-5
Operating ambient temperature max.		°C	40

Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary device for distribution board devices (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecI@ss10.0.1-27-14-35-02 [AKE327013])			
Device fitting			Miniature circuit breaker (MCB)
Additional equipment			Shunt release (for power circuit breaker)
Attached at delivery			No
Assembly width (TE)			1
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of contacts as change-over contact			0
Number of fault-signal switches			0

Rated switch current	A	0
Rated voltage	V	415
Voltage type for actuating		AC/DC
With auto test for earth leakage function		No
Suitable for max. number of poles main contact unit (total)		1
Suitable for max. current main contact unit	A	0

Approvals

Product Standards		IEC/EN 60898; UL 489; CSA-C22.2 No. 5-09; CE marking
UL File No.		E257181
UL Category Control No.		DIHS, DIHS7
CSA File No.		204453
CSA Class No.		1437-01
North America Certification		UL listed, CSA certified
Degree of Protection		IEC: IP20, UL/CSA Type: -

Dimensions

